

## A753 addWAVE GSM/GPRS

The A753 addWAVE GSM/GPRS was developed to meet the most stringent requirements towards a universal telemetry station: high resolution, WMO compliance, synchronous and asynchronous monitoring, lots of memory, 60 I/O channels, and much more. It comes in a robust aluminum housing, with integrated battery and quad-band Motorola GPRS modem. Power is supplied by a solar panel the size of a postcard.

### Applications

- Allround-RTU, extremely compact, extremely rugged, extremely low-power
- WMO-compliant weather recording
- Flood warning, dam monitoring
- Agriculture & public water supply
- Science, research & development, and much more



### Technical data

Dimensions	160 x 60 x 80 mm	Resolution	16-Bit @ 0 - 2,5 V ; 2x 50Hz and 2x 500Hz pulse counter
Weight	1.200gr.	Wind Port C	measures wind 4x per second and calculates 3-sec. average
Ingress Protection class	IP-67	Rain Port D	time stamps every pulse
Temperature range	-30°C to +65°C	Digital events	records and time stamps every status change on a digital input
Case	powder-coated aluminum	Operating time (without charging of internal battery)	in standard mode up to 21 days, in power-save mode up to 6 months; depends on slot-time, transmission rate, and sensors
Screw connections	flange sockets of nickel-plated brass, stainless cover screws	Frequency range	850 / 900 / 1800 / 1900 MHz
Connectors (all connectors IP67 if properly mated or capped)	4x Binder M9 7-pin to sensors 1x Binder M9 5-pin to solar cell / power supply 1x TNC Antenna connector	Rx Sensitivity	-106 dBm
Power supply	6,2 V NiMH battery 3.100 mAh + solar cell / mains adapter	Tx Output Power	max. 2 W (depends on frequency)
I/O-Ports	12x analog in ( 0 - 1/2,5 VDC ; including 3x 0 - 150mV ) 4x pulse counter 4x digital in/out ( 0 - 3V TTL ) 40x SDI-12 values	Transmission distance	max. 36km as per GSM standard
Sensor excitation	- unregulated batt. 5,6V ... 7,2V - regulated from 3,3V ... 5,5V	Expansion (optional)	internal Modbus IF via RS 485
Sampling interval	user specific (from 10sec. to 12h)	Antenna	omnidirectional quad-band, 2dBi
Measuring method	synchronous & asynchronous	Type approvals	R&TTE, FCC Part 15, ACMA Australia, Industry Canada, etc.
Internal memory	2MB for up to 500.000 values	Ordering information:	
		100.753.010	A753 addWAVE GSM/GPRS
		200.733.522	Solar Panel, 460mA