

**SMART WIRELESS SOLUTIONS** 

## A755 GPRS SDI-12

The A755 GPRS SDI provides users with a cost effective means of logging multiparameter sensors which make use of the SDI-12 protocol.

The A755 can record up to 40 SDI-12 sensor values and is also fitted with a single pulse input for connection to rain gauges or flow meters.

The A755 is housed in a robust aluminium case. Sensor and power connections are made using waterproof Binder connectors. Power comes from an internal NiMH battery which is charged using a compact solar panel. A single use Lithium-Thionyl battery is also available.

## Applications

- Weather stations
- Soil moisture monitoring
- Science, research & development, and much more



Dimensions	160 x 60 x 80 mm	Operating time (without charging of internal battery)	in standard mode up to 21 days, in power-save mode up to 6 months; depends on slot-time, transmission rate, and sensors
Weight	1.150 g		
Ingress Protection class	IP-67		
Temperature range	-30°C to +65°C	Frequency range	850 / 900 / 1800 / 1900 MHz
Case	powder-coated aluminum	Rx Sensitivity	-106 dBm
Screw connections	flange sockets of nickel-plated brass, stainless cover screws	Tx Output Power	max. 2 W (depends on frequency)
		Transmission distance	max. 36km as per GSM standard
Connectors (all connectors IP67 if properly mated or	1x Binder M9 7-pin to SDI-12 1x Binder M9 5-pin to solar cell / power supply 1x TNC Antenna connector	Expansion (optional)	internal Modbus IF via RS 485
		Antenna	omnidirectional quad-band, 2dBi
capped)		Type approvals	ACMA Australia, R&TTE,
Power supply	6,2 V NiMH battery 3.100 mAh + solar panel / mains adapter		FCC Part 15, Industry Canada, etc.
		Ordering Information:	
SDI-12 Bus Port	supports up to 40x SDI-12 values	100.755.010	A755 GSM/GPRS SDI
Pulse input	1x pulse counter, max. 30Hz	200.733.522	Solar Panel, 460mA
Sampling interval	user specific (from 10sec. to 12h); sensor restrictions apply	200.800.017 / .018	Cable to SDI-12 sensor, 5m / 10m
		800.000.466	SDI-12 cabling box
Internal memory	2MB for up to 500.000 values	900.000.567	ext. GSM antenna for mast mounting

ADCON TELEMETRY GMBH | Inkustrasse 24 | 3400 Klosterneuburg | Austria

Tel.: +43 (2243) 382 80-0 | Fax: +43 (2243) 382 80-6 | E-Mail: info@adcon.at | Web: http://www.adcon.at

© 05/2009 Adcon Telemetry GmbH | Contents subject to modifications

## Technical data