

2103 Modem Module - Specifications

Size (HxWxD):	2.9 x 9.5 x 7.5 in. (7.4 x 24.1 x 19.1 cm)
Weight:	2 lbs (0.9 kg)
Material:	High-impact polystyrene
Enclosure:	NEMA 4X, 6P and IP68
Operating Temperature:	-4° to 140°F (-20° to 60°C)
Storage Temperature:	-40° to 140°F (-40° to 60°C)
Modulation standards:	Bell 103, Bell 212, V.21, V.22, V.22bis, V.23, V.32, V.32bis, V.34
Error correction standards:	V.42 LAPM, MNP-2, MNP-4, MNP-10
Communication speeds:	0.3, 1.2, 2.4, 4.8, 7.2, 9.6, 12.0, 14.4, 16.8, 19.2, 21.6, 24.0, 26.4, 28.8, 31.2, 33.6 kbps
Data compression standards:	V.42 bis, MNP-5
Power:	9.0 to 16.6V DC, 0.41 mA standby, 141 mA typical
Typical battery life:	50 days (with 2 alkaline batteries)
Setup and data retrieval:	Via IBM PC or compatible computer with Isco Flowlink Software
2191 Battery Module	
Size (H x W x D):	6.0 x 9.6 x 7.6 in. (15.2 x 24.4 x 19.3 cm)
Weight (w/o batteries):	3.2 lbs. 1.4 kg
Enclosure:	NEMA 4X, 6P IP68
Material:	High-impact polystyrene
Batteries:	Two 6V alkaline lantern or lead-acid lantern
Capacity:	Alkaline - 25 Ahrs; Lead Acid - 5 Ahrs