

# Technical Data

## A753 addWAVE GPRS RTU



### A753 addWAVE GPRS RTU

- **Device type**  
Compact data logger with integrated cell modem
- **Product highlights**  
IP-67; ultra-low-power design; WMO compliant measurement methods; high analog resolution; large integrated memory (2MB = ~ 6 months of 15-minute data)
- **Data transmission**  
GSM, GPRS; UMTS optional
- **Sensor interfaces**  
12 x analog 0...1/2,5VDC (3 channels also support 0...150mV); 4 pulse counters (2x 500Hz fast counters / 2x 50Hz counters); 4 digital I/O's (expandable with A553 to up to 52 digital I/O's); 40 SDI-12 values; Modbus via adapter

A753 addWAVE GPRS is an enormously flexible RTU that can be deployed in a wide variety of applications, from agriculture to hydrographics to professional meteorology, from water quality to flood warning, from AMR (Automatic Meter Reading) to leak detection, from the monitoring of solar power to wind energy.

Mechanics:	
Case	Aluminum, powder coated
Protection class	IP-67
Dimensions / weight	160 x 60 x 80 mm / 1.200 gr.

#### 1-3

We reserve the right to make technical changes and improvements without notice. V-29/11/2018  
ADCON Telemetry, Austria

# Technical Data

## A753 addWAVE GPRS RTU

Connectors for sensors and power	4 x M9 female 7-pin to sensor 1 x M9 female 5-pin to power Made in Germany by Binder IP-67 protection class Sockets: brass, nickel plated, with gold plated socket contacts Protective cap
Antenna connector	TNC with external seal, water tight, Made in Germany
Mounting	Mast mounting bracket, integrated
Operating temperature	-20°C ... +65°C / -4°F ... 149°F extended temp. range from -30°C ... +75°C / -22°F ... 167°F upon request

Logger:	
I/O channels	60
Analog inputs	12 x 0...1V/2.5VDC (3 channels on Port C can be programmed to a measuring range of 0...150mV DC low temp. drift with internal amplification)
Digital inputs	40 x SDI-12 Values
Counter inputs	Total of 4 inputs: 2 for standard reed switches, debounced, e.g for rain gauges; max. 50 pulses per second. Min. pulse length 17ms, min. break time 17ms 2 for fast puls generators, e.g. wind speed sensors or flow meters; max. 500 pulses per second. Min. pulse length 1ms, min. break time 1 ms.
TTL In- / Outputs	4 x TTL compatible status inputs or switching outputs, programmable; of which 1 x 5V (Port A) and 3 x 3.3V (all others)
Analog resolution	16-Bit
Sensor excitation voltage	Programmable: - Unregulated battery voltage from 5.5V ... 7.5V - Stabilized voltage, programmable from 3.3V ... 5.5V in 0,1V increments
Memory	2MB for up to 500.000 values, depending on types of sensors attached (SDI-12 typically needs more memory than analog) Example: 15-minute data of an ETo station can be stored for 6 months. 4MB: ex works the A753 can also be equipped with 4MB of memory to double it's storage capacity beyond 1 year for a standard ETo station.

Special Logger functionality:	
Wind gust monitoring	Port C + Adcon wind sensor: 4 samples per second, 4 times per second calculation of 3-second average; Date and time of gust stored

# Technical Data

## A753 addWAVE GPRS RTU

Wind vector monitoring	Port C + Adcon wind sensor: wind direction is measured simultaneously with speed, weighed depending on speed, and stored as a vector
Rain intensity monitoring	Port D + rain gauge with pulse output (max. resolution: 1 second). Date and time of each pulse are stored; in addition up to 3 analog signals and 2 counter inputs can be stored, e.g. wind speed and air temperature
Pressure hammer detection	Port C + Adcon manometer sensor: manometer is permanently excited, sampled 4 x per second, and a 3-second average is stored
Low Voltage amplifier	Port B: sensors with an analog output of 0-150mV can be connected directly; internal amplifier
Asynchronous sampling	To prevent sensors from influencing each others readings when read simultaneously ports can be sampled sequentially
Event-Monitor	To rapidly detect status changes on a digital input it can be sampled up to once per second; date and time of each status change are put in memory; attention: with frequent status changes this can generate a lot of data! Applications: error detection on equipment, access control, pump monitoring, etc.

Data transmission:	
Frequency ranges	900 & 1800 MHz (Europe) and 850 & 1900 MHz (Americas)
Modem	Telit G24 Optional: Telit H24 UMTS 7-Band
SIM-Cards	small form factor
Security	SIM-cards can be PIN-code protected
Connection types	- GSM: CSD Circuit Switched Data - GPRS - UMTS: optional
GPRS connection settings	Programmable: - permanent connection - scheduled connection, from 1 x per minute to 1 x per day
Antenna	Omni directional, vertical, TNC jack, +2dBi

General:	
Power Supply	internal 6.2V battery, charged by solar panel or mains power supply
Battery	Panasonic hi-temperature cell, industry grade, NiMH, 3.300mAh
Type approvals	FCC, R&TTE, CE, Industry Canada, ACMA Australia