



HOBO® BASE-U-4

Optic USB Base Station

The Universal Optic USB Base Station and couplers are used to offload data from any HOBO® data logger with an Optic USB interface. The splash-resistant Optic USB Base Station connects to your computer via USB, while connecting to the data logger via an appropriate coupler. This is compatible with the HOBO UA, U20, U22, U23, UTBI, U24 & U26 series.

NOTE: Couplers for all compatible data loggers are included with the BASE-U-4. Couplers are included for compatibility with six of our most popular data logger types including: UA Pendants, U20 water level data loggers, the U22 Water Temp Pro v2, our UTBI TidbiT, U24 Conductivity and U23 data loggers.



Key Advantages:

- Offload data from any HOBO® data logger with an Optic USB interface
- Couplers are included
- Cable length 183 cm (6 ft.)
- Offloads full 64K logger in 30 seconds

HOBO BASE-U-4 Specifications

Operating temperatures range: 0 to 50°C (32 to 122°F)

Cable length: 183 cm (6 ft.)

Offload rate: Offloads full 64K logger in 30 seconds

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

▶ Email sales@onsetcomp.com

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-800-564-4377

▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

▶ Contact Product Support www.onsetcomp.com/support/contact

▶ Call 1-508-759-9500

▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation

470 MacArthur Boulevard

Bourne, MA 02532