



HOBO[®] MX1101 Data Logger

Temperature/Relative Humidity

Onset's HOBO MX1101 data logger measures and transmits temperature and relative humidity data wirelessly to mobile devices via Bluetooth Low Energy (BLE) technology.

The self-contained wireless data logger works with your mobile device and Onset's free HOBObconnect app so you can configure the logger and read out data over a 100-foot range, with no other dedicated equipment required. Using Onset's free app, you can also view data in graphs, check the operational status of loggers, configure alarm notifications, and share data files.

Add the MX Gateway for remote access to your data in Onset's cloud-based HOBOLink software.

You can download the HOBObconnect app here:

Key Advantages:

- Wireless communication via Bluetooth Low Energy (BLE) technology
- Easy to deploy and offload using free HOBObconnect app
- Visual and audible high & low alarm thresholds
- Stores 84,000 measurements
- Accuracy: +/- 0.2C and +/- 2%RH
- Find me/pager feature
- Patented connectivity technology



HOBO MX1101 Data Logger Specifications

Temperature Sensor

Range	-20° to 70°C (-4° to 158°F)
Accuracy	±0.21°C from 0° to 50°C (±0.38°F from 32° to 122°F)
Resolution	0.024°C at 25°C (0.04°F at 77°F)
Drift	<0.1°C (0.18°F) per year

RH Sensor*

Range	1% to 90%, non-condensing
Accuracy	±2.0% from 20% RH to 80% RH typical to a maximum of ±4.5% including hysteresis at 25°C (77°F); below 20% RH and above 80% RH ±6% typical
Resolution	0.01%
Drift	<1% per year typical

Response Time

Temperature	7:30 minutes in air moving 1 m/s (2.2 mph)
RH	20 seconds to 90% in airflow of 1 m/s (2.2 mph)

Logger

Radio Power	1 mW (0 dBm)
Transmission Range	Approximately 30.5 m (100 ft) line-of-sight
Wireless Data Standard	Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0)
Logger Operating Range	-20° to 70°C (-4° to 158°F); 0 to 95% RH (non-condensing)
Logging Rate	1 second to 18 hours
Logging Modes	Fixed interval (normal, statistics) or burst
Memory Modes	Wrap when full or stop when full
Start Modes	Immediate, push button, date & time, or next interval
Stop Modes	When memory full, push button, date & time, or after a set logging period
Restart Mode	Push button
Time Accuracy	±1 minute per month at 25°C (77°F)

Battery Life 1 year, typical with logging interval of 1 minute. Faster logging and/or statistics sampling intervals, entering burst logging mode, and remaining connected with the app will impact battery life. Excessive readouts, audible alarms, and paging all impact battery life. Visual alarms and other events can have a marginal impact on battery life.

Battery Type Two AAA 1.5 V alkaline batteries, user replaceable

Memory 128 KB (84,650 measurements, maximum)

Full Memory Download Time Approximately 60 seconds; may take longer the further the device is from the logger

LCD LCD is visible from 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range

Size 3.66 x 8.48 x 2.29 cm (1.44 x 3.34 x 0.9 in.)

Weight 56 g (1.98 oz)

Environmental Rating IP50



The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).



*Per RH sensor manufacturer data sheet

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532