



HOBO[®] MX2203 Data Logger

TidbiT MX Temperature 400'

The HOBO MX2203 TidbiT waterproof temperature logger leverages the power of Bluetooth Low Energy (BLE) to deliver high-accuracy temperature measurements straight to your mobile device with Onset's free HOBObconnect app. Designed for durability, this rugged waterproof logger is ideal for long-term deployments in streams, lakes, and oceans (up to 400-foot depths). The HOBO MX2203 also provides the additional feature to detect and record the presence of water which is ideal for monitoring intermittent water applications. Data collection in the field has never been easier!



You can download the HOBObconnect app here:

Key Advantages:

- Convenient wireless setup and download via Bluetooth Low Energy (BLE)
- Large memory stores 96,000 measurements
- Waterproof to 120 meters (400 feet)
- Water detection feature records when logger is in and out of the water
- User-replaceable battery
- Waterproof boot protects the logger during deployment
- LED alarm notifies you when temperature exceeds set threshold
- Battery life extension feature
- Works with Onset's free HOBObconnect app
- $\pm 0.2^{\circ}\text{C}$ ($\pm 0.36^{\circ}\text{F}$) accuracy

HOBO MX2203 Data Logger Specifications

Temperature Sensor (MX2203)

Range MX2203: -20° to 70°C (-4° to 158°F) in air; -20° to 50°C (-4° to 122°F) in water

Accuracy ±0.25°C from -20° to 0°C (±.45°F from -4° to 32°F)
±0.2°C from 0° to 70°C (±0.36°F from 32° to 158°F)

Resolution 0.01°C (0.018°F)

Drift <0.1°C (0.18°F) per year

Response Time MX2203: 17 minutes typical to 90% in air moving 1 m/s, unmounted;
7 minutes typical to 90% in stirred water, unmounted

Logger

Radio Power 1 mW (0 dBm)

Transmission Range Approximately 30.5 m (100 ft) line-of-sight

Wireless Data Standard Bluetooth Smart (Bluetooth Low Energy, Bluetooth 4.0)

Logger Operating Range -20° to 70°C (-4° to 158°F)

Logging Rate 1 second to 18 hours

Buoyancy (Fresh Water) MX2203: 3.1 g (0.11 oz) negative

Waterproof MX2203: To 122 m (400 ft)

Water Detection Water conductivity level of 100 µS/cm or greater necessary for reliable detection of water. Deionized water or water below 100 µS/cm may not be detected.
The water conductivity circuit may not reliably detect water that has frozen around the electrodes, i.e. below 0°C (32°F).

Memory 96,000 measurements

Battery CR2477 3V lithium, user replaceable in MX2203, non-replaceable in MX2204

Battery Life 3 years, typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always On in software.
5 years, typical at 25°C (77°F) with logging interval of 1 minute and Bluetooth Always Off or Bluetooth Off Water Detect in software.
Faster logging intervals and statistics sampling intervals, burst logging, remaining connected with the app, excessive downloads, and paging may impact battery life.
To ensure proper battery installation, see Battery Information for detailed instructions on replacing the battery in the MX2203 logger.

Time Accuracy ± 1 minute per month at 25°C (77°F)

Full Memory Dowload Approximately 45 seconds; may take longer the farther the device is from the logger

Wetted Materials MX2203: Polypropylene case, Delrin® battery cover, EPDM O-ring, stainless steel screws, Santoprene® (TPE) boot

Dimensions MX2203: 4.45 x 7.32 x 3.58 cm (1.75 x 2.88 x 1.41 inches)

Weight MX2203: 36.2 g (1.28 oz)

Environmental Rating IP68



The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532