





# PRODUCT CONFORMITY CERTIFICATE

This is to certify that the

## SITRANS F M MAG 3100 Electromagnetic Flowmeter with MAG 5000, MAG 6000 or MAG 6000 Industry Transmitter

manufactured by:

## Siemens AG,

DE-76181 Karlsruhe Germany

Siemens S.A.S Chemin de la Sandlach, 67500 Haguenau, France

has been assessed by Sira Certification Service and for the conditions stated on this certificate complies with:

**MCERTS Performance Standards for Water Monitoring Equipment Part 3, Version 3 dated July 2018** 

Size range: DN 15 to DN 2000

Certification is awarded in respect of the conditions stated in this certificate

Project No.: 674/0190/70202901 Certificate No: Sira MC080135/11 Initial Certification: 04 November 2008 This Certificate issued: 02 November 2018 Renewal Date: 03 November 2023

**Emily Alexander** 

**Environmental Project Engineer** 

MCERTS is operated on behalf of the Environment Agency by

## Sira Certification Service



Unit 6. Hawarden Industrial Park Hawarden, Deeside, CH5 3US Tel: +44 (0)1244 670 900

The MCERTS certificate consists of this document in its entirety. For conditions of use, please consider all the information within. This certificate may only be reproduced in its entirety and without change To authenticate the validity of this certificate please visit www.csagroupuk.org/mcerts







#### **Certificate Contents**

Approved Site Application	2
Basis of Certification	
Product Certified	
Certified Performance	
Description	
General Notes	

## **Approved Site Application**

The product may be used on all MCERTS applications including abstraction, effluent discharge, ultraviolet disinfection and industrial processing.

Any potential user should ensure, in consultation with the manufacturer, that the product is suitable for the process on which it will be installed.

#### **Field Test Site**

A three month field test was conducted on the final effluent discharge at a municipal waste water treatment plant.

#### **Basis of Certification**

This certification is based on the following Test Report(s) and on Sira's assessment and ongoing surveillance of the product and the manufacturing process.

Sira Evaluation Report MAG 3100 674/0190 dated 04 November 2008







#### **Product Certified**

The measuring system consists of the following parts:

SITRANS F M MAG 3100 electromagnetic flowmeter with MAG 5000, MAG 6000 or MAG 6000 Industry Transmitter

This certificate applies to all instruments fitted with software version:

3.03 X 03 for standard MAG 5000

3.03 X 04 for MAG 5000 C with HART

3.03 X 05 for MAG 5000 CT

3.03 for standard MAG 6000

3.03 X 02 for MAG 6000 CT

3.03 X 01 for MAG 6000 SV

3.04 for MAG 6000 Industry

Serial number (MLFB code) 7ME6310-XXXXa-bXXX-Z [Where X = any figure, a=2 or 3, b=1 or 2] onwards.

DN (mm)	Flow	unit	
	Min	Max	
15	159.1	6361	l/h
25	442.0	17671	l/h
40	1.2	45	m³/h
50	1.8	70	m³/h
65	3.0	119	m³/h
80	4.6	180	m³/h
100	7.1	282	m³/h
125	11.1	441	m³/h
150	16.0	636	m³/h
200	28.3	1130	m³/h
250	44.2	1767	m³/h
300	63.7	2544	m³/h
350	86.6	3463	m³/h
400	113.1	4523	m³/h
450	143.2	5725	m³/h
500	176.8	7068	m³/h
600	254.5	10178	m³/h
700	346.4	13854	m³/h
750	397.7	15904	m³/h
800	452.4	18095	m³/h
900	573.0	22902	m³/h
100	707.0	28274	m³/h
1100	855.3	34211	m³/h
1200	1018.0	40715	m³/h
1400	1385.5	55417	m³/h
1500	1590.5	63617	m³/h
1600	1809.6	72382	m³/h
1800	2290.3	91608	m³/h
2000	2827.5	113097	m³/h







## **Certified Performance**

The instrument was evaluated for use under the following conditions: Ambient Temperature Range: -20°C to +50°C

The instrument meets MCERTS Class 1 requirements for the combined performance characteristic as specified in Table 6 of the MCERTS performance standard. Details of individual performance characteristics are summarised below:

Results are expressed as error % of certification range, unless otherwise stated

Test	Results expressed as error % of reading			error %	Other results	MCERTS specification
	<0.5	<1.0	<1.5	<2.0		
Protection against unauthorised access	Acc	cess to cha	Clause 3.1.2			
Indicating device	The			ates an inc gital outpu	dicating device, at signal	Clause 3.1.3
Units of measurement	Va	arious unit	s of meas	surement a	are available.	Clause 3.1.6
Bi-directional flow	The sign (-) will stand in front of the flow reading when the reading is negative.				Clause 3.1.8	
Combined performance characteristic			1.257			2% Class 1 Table 6
Mean error		-0.68				Clause 6.3.2 ±1.5% Class 1
Repeatability	0.08					Clause 6.3.2 1% Class 1
Supply voltage	0.08					Clause 6.3.3 0.5% Class 1
Output impedance	0.3					Clause 6.3.4 0.5% Class 1
Fluid Temperature	0.15					Clause 6.3.5 0.5% Class 1
Ambient air temperature		0.60				Clause 6.3.6 0.5% Class 1
Relative humidity	0.04					Clause 6.3.6 0.5% Class 1
Stray currents	0.48					Clause 6.3.9 0.5% Class 1
Bi-directional flow Mean error Repeatability	0.046	-0.73				Mean error ±1.5% Class 1 Repeatability 1% Class 1
Loss of Power for electronic flowmeters	No changes in pre set data			data		Clause 6.3.1 to be reported







Test	Results expressed as error % of reading			error %	Other results	MCERTS specification
	<0.5	<1.0	<1.5	<2.0		
Response time					See Note 1	Clause 6.3.19 30 seconds







### **Field Test Results**

The field test was conducted on two MAG 5100 sensors with MAG 6000 transmitters in series and is deemed equivalent by the certification committee for the models stated on this certificate

Test	Results expressed as error % of reading			error %	Other results	MCERTS specification
	<0.5	<1.0	<1.5	<2.0		
Error under field test conditions	Error range 0.29% to 0.61% Field test error is <2% for 100% of readings				Clause 7.3 2% Class 1	
Up time					100%	Clause 7.4 >95%
Maintenance					none	Clause 7.5 to be reported

Note 1: This test has not been conducted.

Note 2:	The following	tests are not	applicable to	the flowmeter:

6.3.7	Incident light	6.3.16	Effect of conduit material
6.3.8	Sensor location	6.3.17	Effect of conduit size
6.3.10	Sonic velocity compensation & response	6.3.18	Fill level
6.3.11	Accuracy of computation	6.3.20	Vibration
6.3.12	User defined stage-discharge equation		







### **Description**

Sitrans FM electromagnetic flow meters included in this certificate consist of a sensor type MAG 3100, in sizes from DN15 to DN2000; and a transmitter, type MAG 5000, MAG 6000 or MAG 6000 Industry. The plug-in transmitters can be integral to the sensor or remote mounted. MAG 3100 sensors are available with a variety of wetted parts so that applications requiring increased corrosion resistance can be accommodated. IP68 versions can be buried or submerged.

The measuring principle is based on Faraday's law of electromagnetic induction. An electrode voltage, proportional to velocity, is generated when a conductive liquid passes through the sensor's magnetic field.

Calibration data, sensor fingerprint, factory and customer settings are stored in a SENSORPROM module, separate from the transmitter. Transmitters can, therefore, be freely exchanged. This technology is proven in use; fitted in Sitrans FM meters for more than 10 years.

Transmitters use low noise high resolution digital signal processors which provide continuous self-monitoring and adjustment of measurement circuits to maintain required accuracy. Plug-in modules for digital communications, e.g. Profibus, can be added at any time during the life of the meter. Transmitter dynamic range is better than 3000:1. Very high input impedance means measurement accuracy is unaffected by liquid conductivity or cable length.

On site verification is achieved using the Siemens FM Verificator; a stand alone field test device, independently calibrated every 12 months. It performs three tests, all referenced to original calibration: Transmitter accuracy, Insulation of measurement circuits, and Sensor magnetism (fingerprint).

Approvals include WRAS for potable water, and OIML R49 pattern approval. Every Siemens flow meter is calibrated at facilities that are individually accredited in accordance with ISO / IEC 17025 by UKAS, DANAK and traceable to NIST.

#### **General Notes**

- 1. This certificate is based upon the equipment tested. The Manufacturer is responsible for ensuring that on-going production complies with the standard(s) and performance criteria defined in this Certificate. The Manufacturer is required to maintain an approved quality management system controlling the manufacture of the certified product. Both the product and the quality management system shall be subject to regular surveillance according to 'Regulations Applicable to the Holders of Sira Certificates'. The design of the product certified is defined in the Sira Design Schedule V03 for certificate No. Sira MC080135/09
- 2. If certified product is found not to comply, Sira Certification Service should be notified immediately at the address shown on this certificate.
- 3. The Certification Marks that can be applied to the product or used in publicity material are defined in 'Regulations Applicable to the Holders of Sira Certificates'.







4. This document remains the property of Sira and shall be returned when requested by the company.